



合创过滤技术（杭州）有限公司
HC filtration (Hangzhou) Co., Ltd

PE-F 聚酯方孔网带数据表

PE-F 聚酯方孔网带								
型号/type	单丝直径/Diameter (mm)		密度/Density yarn(cm)		开孔率	目数	孔径	用途/usage
	经线	纬线	经线	纬线	opening	Mesh	aperture(m	
	Warp	Weft	Warp	Weft	(%)	(inch)	m)	
PE-FK03902	0.9	0.9	3±0.5	3±0.5	49	8	2	造纸烘干 洗浆 污水处理 果蔬输送 无纺布成型 适用于带式 过滤机、带式 压榨机
PE-FHD006	1	1	2.5	2.5	45	6	3	
PE-FK03102	1	1	3±0.5	3±0.5	53	8	1.9	
PE-FK05902	0.9	0.9	5±0.5	5±0.5	20	14	0.80*0.90	
PE-FK04902	0.90	0.90	4.6 ±0.1	4.6 ±0.1	18	12	1.2	
PE-FK06702	0.7	0.7	7±0.5	7±0.5	27	18	0.75	
PE-FK07502	0.5	0.5	7.5±0.5	7.5±0.5	30	19	1	
PE-FK09502	0.5	0.5	10±0.5	10±0.5	25	25	0.5	
PE-FK20252	0.25	0.25	20±0.5	20±0.5	25	50	0.25	
PE-FK09603	0.5	0.6	9	8	29	25	0.30*0.55	
PE-FK05030	0.4	0.40	12±0.5	12±0.5	25	30	0.5	
PE-FK05076	0.2	0.25	29.5-30.5	21.5-22.5	18	76	0.28	
PE-FK05103	0.15	0.20	40	30.7	15	103	0.3	

注：以上产品技术参数为合创过滤平均测试参数，仅供参考

Above data are the averages obtained from a series of typical by HC Filter and are just for reference