



合创过滤技术（杭州）有限公司
HC filtration (Hangzhou) Co., Ltd

DPP 单丝网布数据表

型 号	目 数		丝 经	开孔大小	开孔率	厚度	平方米克重
	(目/每英寸)		(微米)	(微米)	(%)	(微米)	(G/m2)
DPP5	5T	13	450	1550	60	850	259
DPP6	6T	15	400	1270	58	760	246
DPP7	7T	18	350	1080	57	660	220
DPP8	8T	20	350	900	52	660	251
DPP9	9T	23	350	760	47	670	282
DPP10	10S	25	250	750	56	450	160
	10T	25	300	700	49	570	231
DPP12	12S	30	150	680	67	260	69
	12S	30	250	580	48	460	192
	12T	30	300	530	40	580	277
DPP14	14S	36	200	515	52	360	143
DPP15	15S	38	200	470	50	380	154
	15T	38	250	420	40	470	240
DPP16	16T	41	200	425	46	380	164
DPP18	18S	46	150	405	53	260	104
	18T	46	180	375	46	330	150
DPP19	19T	48	150	375	51	260	110
DPP20	20S	50	80	420	71	140	33
	20S	50	110	400	64	180	51
	20T	50	150	350	49	260	115
DPP21	21T	53	150	325	47	270	121
DPP24	24S	61	120	340	67	220	88
	24T	61	150	270	42	280	138
DPP27	27T	68	120	250	46	230	100
DPP28	28S	71	80	280	62	150	46
	28T	71	120	240	45	230	103
DPP29	29T	74	120	225	43	230	107
DPP30	30T	76	120	215	42	230	111
DPP32	32S	80	80	230	54	150	52

	32T	80	100	210	45	180	82
DPP34	34S	86	80	215	53	150	56
	34T	86	100	195	44	180	87
DPP36	36T	91	100	180	42	180	92
DPP39	39S	99	55	200	61	95	30
	39T	99	64	190	55	115	40
DPP40	40T	102	100	150	56	190	103
DPP43	43T	110	80	150	42	155	71
DPP47	47S	120	55	160	57	96	36
	47T	120	64	150	50	120	48
	47HD	120	71	140	43	130	59
DPP49	49S	125	64	140	47	120	50
	49T	125	71	135	44	130	62
DPP53	53S	135	55	135	51	97	40
	53T	135	64	125	44	122	54
DPP59	59S	150	55	115	46	99	45
	59T	150	64	105	38	123	61
DPP64	64S	160	55	100	41	100	48
	64T	160	64	90	33	125	66
DPP72	72S	180	45	95	47	78	37
	72T	180	55	85	38	102	55
DPP77	77T	195	55	75	33	105	58
DPP80	80T	200	45	80	41	80	41
DPP90	90M	230	39	70	40	68	34
	90T	230	45	65	34	82	46
DPP100	100T	250	39	60	36	69	38
DPP110	110T	280	35	56	38	62	34
	110HD	280	39	52	33	70	42
DPP120	120T	305	35	48	33	63	37
	120HD	305	39	44	28	72	46
DPP130	130T	330	35	42	30	58	40
DPP140	140T	355	35	36	25	62	43
DPP150	150T	380	35	32	23	64	46
DPP200	200T	500	35	24	12	78	60

注：以上产品技术参数为合创过滤平均测试参数，仅供参考

Above data are the averages obtained from a series of typical by HC Filter and are just for reference



合创过滤技术（杭州）有限公司
HC filtration (Hangzhou) Co., Ltd

JPP单丝网布数据表

型 号	目 数		丝 经	开孔大小	开孔率	厚度	重量
	(目/每英寸)		(微米)	(微米)	(%)	(微米)	(G/m2)
JPP4	4	10	550	1950	61	950	262
JPP5	5	12	500	1500	56	850	271
JPP6	6	16	400	1267	58	780	208
JPP7	7	18	350	1079	57	675	186
JPP8	8	20	350	900	52	685	212
JPP9	9	24	25	860	60	455	145
JPP10	10	25	300	700	49	576	195
JPP12	12	30	300	533	41	585	234
JPP14	14	35	300	414	34	595	273
JPP16	16	40	250	375	36	485	217
JPP20	20	50	200	300	36	385	173
JPP24	24	60	150	267	41	285	117
JPP28	28	70	120	237	44	215	87
JPP30	30	76	120	213	41	225	94
JPP32	32	80	100	213	46	165	69
JPP36	36	90	100	178	41	178	78
JPP40	40	100	100	150	36	190	87
JPP43	43	110	80	152	43	135	60
JPP48	48	120	80	130	38	145	62
JPP56	56	140	60	120	44	85	44
JPP59	59	150	60	110	42	98	46
JPP64	64	160	60	100	37	105	50
JPP72	72	180	50	90	41	82	39
JPP80	80	200	50	75	36	90	43
JPP100	100	250	40	60	36	65	35
JPP120	120	305	40	43	25	70	42
JPP130	130	330	40	37	23	75	45

注：以上产品技术参数为合创过滤平均测试参数，仅供参考

Above data are the averages obtained from a series of typical by HC Filter and are just for reference